MP45-DU Specification

CPU
Socket P Support Intel Core™ 2 Duo (Penryn) and Celeron M
FSB 1066/800 MHz
CHIPSET
North Bridge: Intel GM45
South Bridge: Intel ICH9M
MEMORY
DDRII SO-DIMM 800/667 x 2 up to 4GB
GRAPHICS
Integrated in Intel GM45 chipset (GFX 500Mhz) DX10
LAN
Intel GbE LAN controller
AUDIO
Realtek HD AUDIO CODEC ALC888
EXPANSION SLOT
mini Card slot x 2
SYSTEM BIOS
Award PnP 4Mb Flash ROM BIOS

FRONT PANEL I/O
USB 2.0 port x 2
Power Button
Power, HDD
REAR PANEL I/O
USB 2.0 port x 6
LAN RJ45 Jack x 1
Audio Jack Stereo x 1 (Line in / Line out / Optical out) / SPDIF via adapter
DVI
eSATA
HDMI via converter
Wireless / TV Tuner antenna hole x 2
DRIVE BAY
For 2.5” S-ATA 2 HDD *1
For Slim Optical Device *1
FORM FACTOR
165 (H) x 165 (L) x 50 (W) mm
Weight : 1.45kg (N.W. of full System)
Volume : 1.36 liters

All specifications above are subject to change without prior notice.

Confidential